

MARK SCHEME for the October/November 2009 question paper

for the guidance of teachers

9709 MATHEMATICS

9709/42

Paper 42, maximum raw mark 50

This mark scheme is published as an aid to teachers and candidates, to indicate the requirements of the examination. It shows the basis on which Examiners were instructed to award marks. It does not indicate the details of the discussions that took place at an Examiners' meeting before marking began, which would have considered the acceptability of alternative answers.

Mark schemes must be read in conjunction with the question papers and the report on the examination.

• CIE will not enter into discussions or correspondence in connection with these mark schemes.

CIE is publishing the mark schemes for the October/November 2009 question papers for most IGCSE, GCE Advanced Level and Advanced Subsidiary Level syllabuses and some Ordinary Level syllabuses.



UNIVERSITY of CAMBRIDGE International Examinations

			mm.m.
Page 2	Mark Scheme: Teachers' version	Syllabus	Papting
	GCE A/AS LEVEL – October/November 2009	9709	42 4th

Cloud.com

Mark Scheme Notes

Marks are of the following three types:

- M Method mark, awarded for a valid method applied to the problem. Method marks are not lost for numerical errors, algebraic slips or errors in units. However, it is not usually sufficient for a candidate just to indicate an intention of using some method or just to quote a formula; the formula or idea must be applied to the specific problem in hand, e.g. by substituting the relevant quantities into the formula. Correct application of a formula without the formula being quoted obviously earns the M mark and in some cases an M mark can be implied from a correct answer.
- A Accuracy mark, awarded for a correct answer or intermediate step correctly obtained. Accuracy marks cannot be given unless the associated method mark is earned (or implied).
- B Mark for a correct result or statement independent of method marks.
- When a part of a question has two or more "method" steps, the M marks are generally independent unless the scheme specifically says otherwise; and similarly when there are several B marks allocated. The notation DM or DB (or dep*) is used to indicate that a particular M or B mark is dependent on an earlier M or B (asterisked) mark in the scheme. When two or more steps are run together by the candidate, the earlier marks are implied and full credit is given.
- The symbol √ implies that the A or B mark indicated is allowed for work correctly following on from previously incorrect results. Otherwise, A or B marks are given for correct work only. A and B marks are not given for fortuitously "correct" answers or results obtained from incorrect working.
- Note: B2 or A2 means that the candidate can earn 2 or 0. B2/1/0 means that the candidate can earn anything from 0 to 2.

The marks indicated in the scheme may not be subdivided. If there is genuine doubt whether a candidate has earned a mark, allow the candidate the benefit of the doubt. Unless otherwise indicated, marks once gained cannot subsequently be lost, e.g. wrong working following a correct form of answer is ignored.

- Wrong or missing units in an answer should not lead to the loss of a mark unless the scheme specifically indicates otherwise.
- For a numerical answer, allow the A or B mark if a value is obtained which is correct to 3 s.f., or which would be correct to 3 s.f. if rounded (1 d.p. in the case of an angle). As stated above, an A or B mark is not given if a correct numerical answer arises fortuitously from incorrect working. For Mechanics questions, allow A or B marks for correct answers which arise from taking *g* equal to 9.8 or 9.81 instead of 10.

			mm m
Page 3	Mark Scheme: Teachers' version	Syllabus	Pap nav sen
	GCE A/AS LEVEL – October/November 2009	9709	
The following	g abbreviations may be used in a mark scheme or used	d on the scripts:	

- AEF Any Equivalent Form (of answer is equally acceptable)
- AG Answer Given on the question paper (so extra checking is needed to ensure that the detailed working leading to the result is valid)
- BOD Benefit of Doubt (allowed when the validity of a solution may not be absolutely clear)
- CAO Correct Answer Only (emphasising that no "follow through" from a previous error is allowed)
- CWO Correct Working Only – often written by a 'fortuitous' answer
- ISW Ignore Subsequent Working
- MR Misread
- PA Premature Approximation (resulting in basically correct work that is insufficiently accurate)
- SOS See Other Solution (the candidate makes a better attempt at the same question)
- SR Special Ruling (detailing the mark to be given for a specific wrong solution, or a case where some standard marking practice is to be varied in the light of a particular circumstance)

Penalties

- MR –1 A penalty of MR –1 is deducted from A or B marks when the data of a question or part question are genuinely misread and the object and difficulty of the question remain unaltered. In this case all A and B marks then become "follow through $\sqrt{2}$ " marks. MR is not applied when the candidate misreads his own figures – this is regarded as an error in accuracy. An MR -2 penalty may be applied in particular cases if agreed at the coordination meeting.
- PA –1 This is deducted from A or B marks in the case of premature approximation. The PA -1 penalty is usually discussed at the meeting.

Page 4		Mark Scheme: Teach				Syllabus	Paptna	
		GCE A/AS LEVEL – Octobe	er/Novei	mbei	2009	9709	42 42	
(i)	(i) $[P = Wsin40^{\circ}]$ P = 7.71		M1 A1	M1		Www.mymaiSyllabusPaperr 2009970942For resolving forces parallel to the plane or for a correct triangle of forces or for resolving horizontally and vertically		
(ii)	$[P\cos 40^{\circ}]$ $P = 10.1$	= Wsin40°]	M1 A1	2				
(i)	Loss in P	E is 2.7×10^{6} J	B1	1				
(ii)	WD is 2.1	$1 \times 10^6 \text{ J}$	B1ft	1	ft incorr	ect loss in PE		
(iii)		$ge = \frac{1}{2} \frac{15000(16^2 - 14^2)}{15000(16^2 - 14^2) + 1600 \times 2500]}$ $45 \times 10^6 \text{ J}$	B1 M1 A1	3	WD by DF = Gain in KE + WD by resistance SR for candidates who use Newton's Law method instead of energy (max 1/3) $a = (16^2 - 14^2)/(2 \times 2500) = 0.012$ DF = 1600 + 15000 × 0.012 = 1780 WD = 1780 × 2500 = 4.45 × 10 ⁶ B1			
(i)	DF = 240	0 at max speed] 000/v] nnot exceed 40 ms ⁻¹	M1 M1 A1	3	For using $DF = R$ at max. speed For using $DF = P/v$ AG			
(ii)		ma] -600 = 1250a ion is 0.8 ms ⁻²	M1 A1 A1	3	For using Newton's second law			
(i)	[1.2 = mg Mass is 0		M1 A1	2	For resolving forces normal to the plane			
(ii)	- 0.125 ×	x - F = ma] 10 × 0.28 - 0.4 = 0.125a deceleration is 6 ms ⁻²	M1 A1ft A1	3		g Newton's secor ect mass	nd law	
(iii)	µR > mg	sin $\alpha \rightarrow$ particle remains at rest	M1 A1	2		paring magnitude sinα (0.35)	es of µR (0.4)	

Page 5	Mark Scheme: Teache	ers' ver	sion		Syllabus	Papt
	GCE A/AS LEVEL – October	r/Nover	nber	[.] 2009	9709	Paperson Pap
•				F 1		11
i) 12 + 15si	$-20^{\circ} - \mathbf{B}$	M1		For resol	ving forces vertic	cally
$F = 15\cos^{-1}{2}$		Al D1				
		B1 M1		Eanning	E/D	
	s30°/(12 + 15sin30°] nt is 0.666	A1	5	For using AG	$\mu - \Gamma/K$	
Coefficie	11 15 0.000	AI	5	AU		
ii) F = 0.666	(12 – 15sin30°)	B1				
		M1		For using	, Newton's secon	d law
	-F = 1.2a	A1				
Accelerat	ion is 8.33 ms ^{-2}	A1	4			
)					ving Newton's se	cond law to A
		1.61			r for using	
T A		M1		(M + m)a	a = (M - m)g	
-	= 0.3a and $0.7g - T = 0.7a$ or (0.7 + 0.3)a = (0.7 - 0.3)g	A1				
Accelerat	ion is 4 ms^{-2}	A1	3			
) $s_1 = 1.6^2/($	2 × 4)	B1ft		ft acceler		
		M1			$g 0^2 = 1.6^2 - 2gs_2$	
Height is	0.448 m	A1	3	From s ₁ -	$s_2 = 0.32 + 0.12$	8
) $t_1 = 1.6/4$		B1ft		ft acceler	ation	
				(can be s	cored in (ii))	
		M1			$g 0 = 1.6 - gt_2$	
Time take	en is 0.56 s	A1	3	From t_1 +	$t_2 = 0.4 + 0.16$	
 Iternative f	or part (iii))	• •	•			
	or Part (III)			For obser	ving that the ave	rage sneed is
					for each of the tv	
				equal to		r r
		M1		(0+1.6)/	2 ms^{-1}	
$t_1 + t_2 = (s_1 + t_2)$	$(+ s_2)/0.8$	A1		х — <i>Р</i>		
me taken is		A1	3			
					y for finding s ₁ + fore ans (ii)]	s ₂ if ans(iii) is
lternatively	y for parts ii and iii using v–t graph)					
		M1		Use of or	adient to find t_1 c	or t ₂
				D		· 2
= 1.6/4 and 1		A1				
me taken is	0.56s	A1				
					f area to find	
_		M1		$s_1 \text{ or } s_2 \text{ or }$	$s_1 + s_2$	
$= 0.4 \times 1.6/2$	$2 \text{ or } s_2 = 0.16 \times 1.6/2 \text{ or } c_1 = 0.16 \times 1.6/2 \text{ or } c_2 = 0.1$, -				
eight is 0.44	$s_1 + s_2 = (0.4 + 0.16) \times 1.6/2$	A1	-			
	2.00	A1	6			

Page 6	Mark Scheme: Tea	chers' ver	sion		Syllabus	Papto
	GCE A/AS LEVEL – Octo	ber/Nover	nber	2009	9709	42 41
(i)		M1		Forusin	$g v(t) = \dot{s}(t)$	Pap nating
v = 1.2t -	$-0.012t^2$	A1		1 of usin	g(t) = s(t)	
v 1.2t	0.0121	711		For usin	$g a(t) = \dot{v}(t) and$	evaluating
[a(50) =	$1.2 - 0.024 \times 50$]	M1		a(50)		evaluating
a = 0		A1		AG		
V = 30		B1	5	_		
$(\mathbf{i}) = -0.6$	$550^2 - 0.004 \times 50^3$ (= 1000)	D1				
• /	· · · · · · · · · · · · · · · · · · ·	B1		Forusin	g 'average speed	– total distance
$\frac{1000 + 50}{50 + 6}$	$\frac{s_2}{2} = 27.5$	M1		/total tin	• • •	
$\begin{bmatrix} 30 + l \end{bmatrix}$	2	1011				1
$[1000 \pm 3]$	$20t = 27.5(50 \pm t)$	M1			stituting $s_2 = Vt_2$ a	nd attempting
$t_2 = 150$	$30t_2 = 27.5(50 + t_2)]$	A1		to solve	10 t_2	
$t_2 = 130$ t = 200		A1 A1	5	ft 50 + t.	2 (requires both M	(marks)
t = 200		Π1	5	$11.50 + t_2$,
(Alternative	for part (ii))		•			
	-0.004×50^3 (= 1000)	B1				
•	× ,			For usin	g 'average speed	= total distance
$[(1000 + s_2)/t]$	= 27.5]	M1		/total tin	ne' with $t_2 = t - 50$)
(1000 + 30(t -	(-50))/t = 27.5	Alft		(ft V and	$d \mathbf{s}_1$)	
[27.5t = 1000]	+30(t-50)]	M1		For atter	npting to solve fo	rt
t = 200		A1	5		1 8 1 1 1 1 1 1	