



## **Cambridge International Examinations**

Cambridge International Advanced Subsidiary and Advanced Level

MATHEMATICS
Paper 4
October/November 2016
MARK SCHEME
Maximum Mark: 50
Published

This mark scheme is published as an aid to teachers and candidates, to indicate the requirements of the examination. It shows the basis on which Examiners were instructed to award marks. It does not indicate the details of the discussions that took place at an Examiners' meeting before marking began, which would have considered the acceptability of alternative answers.

Mark schemes should be read in conjunction with the question paper and the Principal Examiner Report for Teachers.

Cambridge will not enter into discussions about these mark schemes.

Cambridge is publishing the mark schemes for the October/November 2016 series for most Cambridge IGCSE<sup>®</sup>, Cambridge International A and AS Level components and some Cambridge O Level components.

® IGCSE is the registered trademark of Cambridge International Examinations.



			·	2
Page 2	Mark Scheme	Syllabus	Pilly	O PAR
	Cambridge International AS/A Level – October/November 2016	9709	42	70 0

## **Mark Scheme Notes**

Marks are of the following three types:

- M Method mark, awarded for a valid method applied to the problem. Method marks are not lost for numerical errors, algebraic slips or errors in units. However, it is not usually sufficient for a candidate just to indicate an intention of using some method or just to quote a formula; the formula or idea must be applied to the specific problem in hand, e.g. by substituting the relevant quantities into the formula. Correct application of a formula without the formula being quoted obviously earns the M mark and in some cases an M mark can be implied from a correct answer.
- A Accuracy mark, awarded for a correct answer or intermediate step correctly obtained.

  Accuracy marks cannot be given unless the associated method mark is earned (or implied).
- B Mark for a correct result or statement independent of method marks.
- When a part of a question has two or more "method" steps, the M marks are generally independent unless the scheme specifically says otherwise; and similarly when there are several B marks allocated. The notation DM or DB (or dep\*) is used to indicate that a particular M or B mark is dependent on an earlier M or B (asterisked) mark in the scheme. When two or more steps are run together by the candidate, the earlier marks are implied and full credit is given.
- The symbol 
   <sup>↑</sup> implies that the A or B mark indicated is allowed for work correctly following on from previously incorrect results. Otherwise, A or B marks are given for correct work only. A and B marks are not given for fortuitously "correct" answers or results obtained from incorrect working.
  - Note: B2 or A2 means that the candidate can earn 2 or 0. B2/1/0 means that the candidate can earn anything from 0 to 2.

The marks indicated in the scheme may not be subdivided. If there is genuine doubt whether a candidate has earned a mark, allow the candidate the benefit of the doubt. Unless otherwise indicated, marks once gained cannot subsequently be lost, e.g. wrong working following a correct form of answer is ignored.

- Wrong or missing units in an answer should not lead to the loss of a mark unless the scheme specifically indicates otherwise.
- For a numerical answer, allow the A or B mark if a value is obtained which is correct to 3 s.f., or which would be correct to 3 s.f. if rounded (1 d.p. in the case of an angle). As stated above, an A or B mark is not given if a correct numerical answer arises fortuitously from incorrect working. For Mechanics questions, allow A or B marks for correct answers which arise from taking g equal to 9.8 or 9.81 instead of 10.

			·17.	2
Page 3	Mark Scheme	Syllabus	Pilh	
	Cambridge International AS/A Level – October/November 2016	9709	42	Ary Or

The following abbreviations may be used in a mark scheme or used on the scripts:

AEF/OE	Any Equivalent Form (of answer is equally acceptable) / Or Equivalent
AG	Answer Given on the question paper (so extra checking is needed to ensure that the detailed working leading to the result is valid)
CAO	Correct Answer Only (emphasising that no "follow through" from a previous error is allowed)
CWO	Correct Working Only – often written by a 'fortuitous' answer
ISW	Ignore Subsequent Working
SOI	Seen or implied
SR	Special Ruling (detailing the mark to be given for a specific wrong solution, or a case where some standard marking practice is to be varied in the light of a particular circumstance)

## **Penalties**

- PA –1 This is deducted from A or B marks in the case of premature approximation. The PA –1 penalty is usually discussed at the meeting.

					P. M. W.
Page	4 Mark S	cheme		Syllabus	P. May
	Cambridge International AS/A L	.evel – October/N	November 2016	9709	42 4/70 15
					42 Msc/040
1 (i)	$3.5 = 10a \rightarrow a = 0.35 \mathrm{ms}^{-2}$	B1	Allow $a = 3$ .	5/10	Ad. COM
	$[10\cos 15 - F = 2 \times 0.35]$		For applying	Newton's 2	

1	(i)	$3.5 = 10a \rightarrow a = 0.35 \text{ms}^{-2}$	B1		Allow $a = 3.5/10$
		$[10\cos 15 - F = 2 \times 0.35]$	M1		For applying Newton's 2nd law to the particle
		$F = 8.96 \mathrm{N}$ AG	A1	[3]	
		Alternative	to 1(i)		
		$s = \frac{1}{2}(0 + 3.5) \times 10 = 17.5 \mathrm{m}$	B1		Distanced moved in 10 secs
		$[10\cos 15 \times 17.5 = F \times 17.5 + \frac{1}{2} \cdot 2 \cdot (3.5)^{2}]$	M1		Work done by 10 N force = WD against F + KE gain
		$F = 8.96 \mathrm{N}$ AG	<b>A1</b>	[3]	
	(ii)	$[R = 2g - 10\sin 15]$	M1		Resolving forces vertically
		$[\mu = 8.96/(2g - 10\sin 15)]$	M1		Using $F = \mu R$
		$\mu = 0.515$	<b>A1</b>	[3]	
2	(i)	$[v = 4t - 40t^{0.5}]$	M1*		For differentiating s to find v
		$[a = 4 - 20t^{-0.5}]$	M1*		For differentiating <i>v</i> to find <i>a</i>
		$[4 - 20t^{-0.5} = 0]$	DM1		For setting $a = 0$ and attempt to solve to find $t$
		$t = 25 \mathrm{s}$	A1	[4]	
	(ii)	Substitute their <i>t</i> into <i>s</i> <b>or</b> <i>v</i>	M1		
		Displacement= $-2083.3 \text{ m} (= -2080 \text{ 3sf})$ <b>and</b> Velocity = $-100 \text{ ms}^{-1}$	<b>A1</b>	[2]	or Displacement = $-6250/3$

			1.3. M	
Page 5	Mark Scheme	Syllabus	Pryna	The state of
	Cambridge International AS/A Level – October/November 2016	9709	42 PH	S

		T	1	1	
3	(i)	$[X = 60\cos 25 + 50\cos 15]$	M1		For resolving both forces in the direction of river
		$= 103 \mathrm{N}$	A1	[2]	Value of $X$ is 102.7 N
	(ii)	$Y = 60\sin 25 - 50\sin 15 \ [= 12.4]$	B1		Component perpendicular to the direction of the river
		$[R^{2} = X^{2} + Y^{2}]$ or $[\alpha = \arctan(Y/X)]$	M1		For using Pythagoras or for using arctan to find the resultant force or its direction
		Magnitude is $103 \mathrm{N}$ (or $\alpha = 6.9^{\circ}$ with direction specified unambiguously)	A1		Magnitude is 103.4N
		$\alpha = 6.9^{\circ}$ with direction specified unambiguously (or Magnitude = 103 N)	B1	[4]	
4	(i)	$PE loss = mg \times 100 sin 20$	B1		
		$\left[ \frac{1}{2}mv^2 - \frac{1}{2}m \times 5^2 = mg \times 100\sin 20 \right]$	M1		Using KE gain = PE loss
		$v = 26.6 \mathrm{ms}^{-1}$	A1	[3]	
		Alternative met	hod for 4	l(i)	
		$a = g \sin 20 $ [ = 3.42]	B1		
		$[v^2 = 5^2 + 2 \times a \times 100]$	M1		Using $v^2 = u^2 + 2as$
		$v = 26.6 \mathrm{ms}^{-1}$	A1	[3]	
	(ii)	KE = $\pm (0.5m \times 441 - 0.5m \times 25) [= \pm 208m]$	В1		
		$[mg \times 100\sin 20 = 8500 + 208m]$	M1		For using PE loss = WD against Friction + KE gain
		Mass m = 63.4 kg	A1	[3]	

					P. Mathscloud
Page 6	Mark Scheme	,		Syllabus	P. The Say
	Cambridge International AS/A Level -	9709	42 9/70 15		
					00/0
5	$F = \mu mg \cos 30$	B1			AD.COM
	$[10 + F - mg\sin 30 = 0]$	M1	Resolving up	, first case	

5	$F = \mu mg \cos 30$	B1		
	$[10 + F - mg\sin 30 = 0]$	M1		Resolving up, first case
	$[75 - F - mg\sin 30 = 0]$	M1		Resolving up, second case
	[85 = 2 $mg$ sin30] or [10 + $\mu mg$ cos30 - $mg$ sin30 = 0 75 - $\mu mg$ cos30 - $mg$ sin30 = 0]	M1		Either attempt to solve for $m$ or Solve a pair of two 3 term simultaneous equations for either $m$ or $\mu$
	$m = 8.5 \mathrm{kg} \mathrm{or} \mu = 0.442$	A1		
	$\mu = 0.442 \text{ or } m = 8.5 \text{ kg}$	B1	[6]	
6 (i)	$[Power = 400 \times 25]$	M1		For using $P = Fv$ where $F = \text{resistance} = 400 \text{N}$
	Power = 10000 W	A1	[2]	Allow 10 kW
(ii)	Tension = 100 N	B1	[1]	Considering the trailer
(iii)	New driving force = 25000/20 = 1250 N	B1		Driving force = $P/v$ at the instant when $v = 20$
	[DF $-300 - T - 3000 \text{ gsin4} = 3000a$ ] or [T - 100 - 500  gsin4 = 500a] or [DF $-400 - 3500 \text{ gsin4} = 3500a$ ]	M1		For using Newton's second law applied <b>either</b> to the van <b>or</b> to the trailer <b>or</b> to the system of van and trailer.
	[21 5000 80m. 5000m]	M1		For using N2 applied to one of the other cases
	[ $a = -0.4547$ may be seen]	M1		Solving or using substitution to find <i>T</i>
	T = 221  N	A1	[5]	Allow $T = 1550/7 \text{N}$

			3, 3
Page 7	Mark Scheme	Syllabus	P. Than Air
	Cambridge International AS/A Level – October/November 2016	9709	42

7	(i)	$v = 3 \times 10 = 30 \mathrm{ms}^{-1}$	B1		Velocity after 10 seconds
		$[s = \frac{1}{2} (30 + 40) \times 30]$ or equivalent complete method	M1		For determining distance travelled in first 40 seconds
		Total distance = 1050 m	A1	[3]	
	(ii)	[Distance = 450 m Time taken = 450/15 = 30 s]	M1		For finding distance covered in deceleration stage and time taken for this stage
		Total time of motion for $car = 70 s$	A1		May be implied by time for motorcycle = 50 s
		[Motorcycle takes 50 s to travel 1500 m $1500 = \frac{1}{2}(30 + 50) \times V$ or $1500 = 30 V + 0.5 \times 20 V$ ]	M1		For setting up an equation for distance travelled by $M/C$ ( $v$ – $t$ graph or other) involving $V$ or $a$ and up to one other variable.
		$V = 37.5 \mathrm{ms}^{-1}$	A1		
		[20 s is split between 5 s accelerating and 15 s decelerating]	M1		For finding time taken to accelerate to speed $V$
		$a = 37.5/5 = 7.5 \mathrm{ms}^{-2}$	A1	[6]	
(	(iii)	Displacement-time graph	B1		Two of the three graph stages correct with correct curvature
			B1		All three stages of the graph correct with correct curvature
			B1	[3]	Correct graph, fully labelled t=10,40,70s = 150,1050, 1500