

**Mathematics (MEI)**

Advanced GCE

Unit **4762**: Mechanics 2

**Mark Scheme for June 2013**

---

OCR (Oxford Cambridge and RSA) is a leading UK awarding body, providing a wide range of qualifications to meet the needs of candidates of all ages and abilities. OCR qualifications include AS/A Levels, Diplomas, GCSEs, Cambridge Nationals, Cambridge Technicals, Functional Skills, Key Skills, Entry Level qualifications, NVQs and vocational qualifications in areas such as IT, business, languages, teaching/training, administration and secretarial skills.

It is also responsible for developing new specifications to meet national requirements and the needs of students and teachers. OCR is a not-for-profit organisation; any surplus made is invested back into the establishment to help towards the development of qualifications and support, which keep pace with the changing needs of today's society.

This mark scheme is published as an aid to teachers and students, to indicate the requirements of the examination. It shows the basis on which marks were awarded by examiners. It does not indicate the details of the discussions which took place at an examiners' meeting before marking commenced.

All examiners are instructed that alternative correct answers and unexpected approaches in candidates' scripts must be given marks that fairly reflect the relevant knowledge and skills demonstrated.

Mark schemes should be read in conjunction with the published question papers and the report on the examination.

OCR will not enter into any discussion or correspondence in connection with this mark scheme.

© OCR 2013

## Annotations and abbreviations

Annotation in scoris	Meaning
✓ and ✗	
BOD	Benefit of doubt
FT	Follow through
ISW	Ignore subsequent working
M0, M1	Method mark awarded 0, 1
A0, A1	Accuracy mark awarded 0, 1
B0, B1	Independent mark awarded 0, 1
SC	Special case
^	Omission sign
MR	Misread
Highlighting	

Other abbreviations in mark scheme	Meaning
E1	Mark for explaining
U1	Mark for correct units
G1	Mark for a correct feature on a graph
M1 dep*	Method mark dependent on a previous mark, indicated by *
cao	Correct answer only
oe	Or equivalent
rot	Rounded or truncated
soi	Seen or implied
www	Without wrong working

**Subject-specific Marking Instructions for GCE Mathematics (MEI) Mechanics strand**

- a. Annotations should be used whenever appropriate during your marking.

**The A, M and B annotations must be used on your standardisation scripts for responses that are not awarded either 0 or 1 mark.** It is vital that you annotate standardisation scripts fully to show how the marks have been awarded.

For subsequent marking you must make it clear how you have arrived at the mark you have awarded.

- b. An element of professional judgement is required in the marking of any written paper. Remember that the mark scheme is designed to mark correct solutions. Correct *solutions* leading to correct answers are awarded full marks but work must not be judged on the answer alone, and answers that are given in the question, especially, must be validly obtained; key steps in the working must always be looked at and anything unfamiliar must be investigated thoroughly.

Correct but unfamiliar or unexpected methods are often signalled by a correct result following an *apparently* incorrect method. Such solutions must be carefully assessed. When a candidate adopts a method which does not correspond to the mark scheme, award marks according to the spirit of the basic scheme; if you are in any doubt whatsoever (especially if several marks or candidates are involved) you should refer to your Team Leader.

- c. The following types of marks are available.

**M**

A suitable method has been selected and *applied* in a manner which shows that the method is essentially understood. Method marks are usually lost for numerical errors, algebraic slips or errors in units. However, it is not usually sufficient for a candidate just to indicate an intention of using some method or just to quote a formula; the formula or idea must be applied to the specific problem in hand, e.g. by substituting the relevant quantities into the formula. In some cases the nature of the errors allowed for the award of an M mark may be specified.

**A**

Accuracy mark, awarded for a correct answer or intermediate step correctly obtained. Accuracy marks cannot be given unless the appropriate Method mark is earned (or implied). Therefore M0 A1 cannot ever be awarded.

**B**

Mark for a correct result or statement independent of Method marks.

**E**

A given result is to be established or a result has to be explained. This usually requires more working or explanation than the establishment of an unknown result.

Unless otherwise indicated, marks once gained cannot subsequently be lost, eg wrong working following a correct answer. Sometimes this is reinforced in the mark scheme by the abbreviation isw. However, this would not apply to a case where a candidate follows through the correct answer as part of a wrong argument.

- d. When a part of a question has two or more 'method' steps, the M marks are in principle independent unless the scheme specifies otherwise; and similarly where there are several B marks allocated. (The notation 'dep \*' is used to indicate that a particular mark is dependent on an earlier, asterisked, mark in the scheme.) Of course, in practice it may happen that when a candidate has once gone wrong on a part of a question, the work from there on is worthless so that no more marks can sensibly be given. On the other hand, when two steps are successfully run together by the candidate, the earlier marks are implied and full credit must be given.
- e. The abbreviation ft implies that the A or B mark indicated is allowed for work correctly following on from previously incorrect responses. Otherwise, A and B marks are given for correct work only — differences in notation are of course permitted. A (accuracy) marks are given for answers obtained from incorrect working. When A or B marks are awarded for work at an intermediate stage of a solution, there may be various alternatives that are equally acceptable. In such cases, exactly what is acceptable will be detailed in the mark scheme rationale. If this is not the case please consult your Team Leader.

Sometimes the answer to one part of a question is used in a later part of the same question. In this case, A marks will often be 'followed through'. In such cases you must ensure that you refer back to the answer of the previous part question even if this is not shown on the image zone. You may find it easier to mark follow through questions candidate-by-candidate rather than question-by-question.

- f. Unless units are specifically requested, there is no penalty for wrong or missing units as long as the answer is numerically correct and expressed either in SI or in the units of the question. (e.g. lengths will be assumed to be in metres unless in a particular question all lengths are in km, when this would be assumed to be the unspecified unit.)

We are usually quite flexible about the accuracy to which the final answer is expressed and we do not penalise over-specification.

#### **When a value is given in the paper**

Only accept an answer correct to at least as many significant figures as the given value. This rule should be applied to each case.

#### **When a value is not given in the paper**

Accept any answer that agrees with the correct value to 2 s.f.

ft should be used so that only one mark is lost for each distinct error made in the accuracy to which working is done or an answer given. Refer cases to your Team Leader where the same type of error (e.g. errors due to premature approximation leading to error) has been made in different questions or parts of questions.

There are some mistakes that might be repeated throughout a paper. If a candidate makes such a mistake, (eg uses a calculator in w

angle mode) then you will need to check the candidate's script for repetitions of the mistake and consult your Team Leader. A penalty should be given.

There is no penalty for using a wrong value for  $g$ . E marks will be lost except when results agree to the accuracy required.

g. Rules for replaced work

If a candidate attempts a question more than once, and indicates which attempt he/she wishes to be marked, then examiners should mark the candidate requests.

If there are two or more attempts at a question which have not been crossed out, examiners should mark what appears to be the last (complete) attempt and ignore the others.

NB Follow these maths-specific instructions rather than those in the assessor handbook.

h. For a *genuine* misreading (of numbers or symbols) which is such that the object and the difficulty of the question remain unaltered according to the scheme but following through from the candidate's data. A penalty is then applied; 1 mark is generally appropriate. This may differ for some units. This is achieved by withholding one A mark in the question.

Marks designated as cao may be awarded as long as there are no other errors. E marks are lost unless, by chance, the given results established by equivalent working.

'Fresh starts' will not affect an earlier decision about a misread.

Note that a miscopy of the candidate's own working is not a misread but an accuracy error.

i. If a graphical calculator is used, some answers may be obtained with little or no working visible. Allow full marks for correct answers (provided, of course, that there is nothing in the wording of the question specifying that analytical methods are required). Where an answer is wrong but there is some evidence of method, allow appropriate method marks. Wrong answers with no supporting method scores in doubt, consult your Team Leader.

j. If in any case the scheme operates with considerable unfairness consult your Team Leader.

Question			Answer	Marks	
1	(a)	(i)	$3 \times 4 + 21 \times 2 = 4U$ $4U = 54$ so $U = 13.5$ and speed is $13.5 \text{ m s}^{-1}$  <b>OR</b> $21 = 4a$ : $a = 5.25$ and $v = 3 + 2 \times 5.25$ speed is $13.5 \text{ m s}^{-1}$	M1 A1 <b>[2]</b> M1 A1 <b>[2]</b>	Use of PCLM and $I = Ft$  Use of $F = ma$ and <i>suvat</i>
1	(a)	(ii)	Let $V$ be the speed of S in direction PQ $54 - 2 \times 3 = (4 + 2)V$ $6V = 48$ so $V = 8$ and velocity is $8 \text{ m s}^{-1}$ in direction PQ	M1 E1 <b>[2]</b>	PCLM for coalescence Answer given. Accept no reference to direction.
1	(a)	(iii)	Let velocities of R be $u$ before and $v$ after, both in the direction SR $6 \times 8 + 4u = 6 \times 5 + 4v$ $v - u = 4.5$ $\frac{v-5}{u-8} = -\frac{1}{4}$ $4v + u = 28$ Solving $u = 2$ so $2 \text{ m s}^{-1}$ in the direction SR $v = 6.5$ so $6.5 \text{ m s}^{-1}$ in the direction SR	M1 A1 M1 A1 A1 A1 <b>[6]</b>	Use of PCLM. Allow any sign convention. All marks to be correct. Any form. Use of NEL correct way up; allow sign errors Any form signs consistent with PCLM eqn cao <b>NOTE that a sign error in NEL leads to <math>u =</math></b> cao. Withhold only 1 of the final A marks if the direction Directions can be inferred from a CLEAR diagram

Question	Answer	Marks	Guidance
1 (b) (i)	Find $v$ , the speed at which particle hits the plane $\frac{1}{2} \times 0.2 \times v^2 - \frac{1}{2} \times 0.2 \times 5^2 = 0.2 \times 10 \times 10$ so $v^2 = 225$ and $v = 15$ $\cos \alpha = \frac{4}{5}$ , $\sin \alpha = \frac{3}{5}$ Let velocity after be at $\beta$ to the plane Parallel to the plane $15 \cos \alpha = 13 \cos \beta$  So $\cos \beta = \frac{12}{13}$ and $\beta = 22.61^\circ$ .. so $22.6^\circ$ (3 s. f.) Perpendicular to the plane: $13 \sin \beta = e \times 15 \sin \alpha$  $\sin \beta = \frac{5}{13}$ so $13 \times \frac{5}{13} = 15 \times \frac{3}{5} \times e$ and $e = \frac{5}{9}$	M1 A1 B1  M1  A1 M1  A1 A1  <b>[8]</b>	Use of WE or <i>suvat</i> must use distance of ... Answer not required ( $v = 14.9$ if $g = 9.8$ ) Use of either expression or use of $36.9^\circ$  Attempt to conserve velocity component parallel to ... Allow use of 5 instead of 15  ( $\beta = 23.8^\circ$ if $g = 9.8$ ) Attempt to use NEL perpendicular to plane: Allow ... or use $\tan \beta = e \tan \alpha$ o.e. find $\tan \beta = \frac{5}{12}$ cao Accept 0.56 ( $e = 0.589$ if $g = 9.8$ )
	OR: First three marks as above  Parallel to plane, $u_x = 15 \cos \alpha (= 12)$ and $v_x = u_x (= 12)$ $\cos \beta = \frac{v_x}{v} = \frac{12}{13}$ $\beta = 22.6^\circ$ Perpendicular to plane, $u_y = 15 \sin \alpha (= 9)$ and $v_y = e u_y (= 9e)$ $v_x^2 + v_y^2 = 13^2$ $12^2 + (9e)^2 = 13^2$ so $e^2 = \frac{25}{81}$ $e = \frac{5}{9}$	M1A1B1  M1 A1  M1  A1 A1  <b>[8]</b>	Attempt to conserve velocity component parallel to ... Allow use of 5 instead of 15  Attempt to use NEL perpendicular to plane. Allow use of 5 instead of 15  Use Pythagoras' theorem for velocities after collision

Question		Answer	Marks	
1	(b) (ii)	Impulse is perp to plane with mod $0.2(13 \sin \beta - (-15 \sin \alpha)) = 0.2(5 - (-9))$ $= 2.8 \text{ N s}$	M1 A1 [2]	For use of $I = m(v - u)$ perp to the plane cao
2	(i)	WD is $800 \times 9.8 \times 6 + 400 \times 6 \text{ J}$  $= 49\,440$ Power is $49440 \div 12$ $= 4120 \text{ W}$	M1  E1 M1 A1 [4]	WD as $Fd$ Used in TWO terms  Power is $WD / \Delta t$ cao
2	(ii)	Power is $(800 \times 9.8 + 400) \times 0.55$  $= 4532 \text{ W}$	M1 A1 A1 [3]	Power as $Fv$ in one term All correct cao
2	(iii)	Let speed be $v$ $\frac{1}{2} \times 800v^2 = 800 \times 9.8 \times 3 - 400 \times 3$  $v^2 = 55.8$ so $v = 7.4699\dots$  and speed is $7.47 \text{ m s}^{-1}$ (3 s.f.)	M1 A1 A1  A1 [4]	Use of W-E equation Must include KE and at least one WD term Allow only sign errors All correct  SC: Use of N2L and <i>suvat</i> : M1 Complete method A1 7.47 cao
2	(iv)	$\frac{1}{2} \times 800 \times \frac{v^2}{4} - \frac{1}{2} \times 800 \times v^2$  $= (800 \times 9.8 - 400) \times 0.8$ - WD  WD is 22 692 so 22 700 J (3 s. f.)	M1  B1 B1 A1  A1 [5]	Use of W-E equation Must include 2 KE terms and one WD term Final KE term correct. FT their $v$ . One correct WD term All terms present. Allow sign errors and FT their $v$ . cao SC Use of N2L and <i>suvat</i> : Award maximum of B1 for 'Average force (28365

Question		Answer	Marks	
3	(i)	c.w. moments about A $60\cos 40 \times 0.3 - 60\sin 40 \times 0.1$  $= 9.93207\dots$ so 9.93 N m (3 s. f.)	M1 A1 E1 <b>[3]</b>	Condone using cm not m in moments in oe e.g. $60(0.3 - 0.1\tan 40)\sin 50$ or $60 \times \frac{1}{\sqrt{10}}$ Method of dealing with moment of weight. Allow Both weight terms correct. Allow wrong overall sign with the same sign
3	(ii)	$P\cos 40 \times 0.2 - 9.93207\dots = 0$ $P = 64.827\dots$ so 64.8 (3 s. f.)	M1 A1 <b>[2]</b>	Moments of all relevant forces attempted. No extra $\cos \leftrightarrow \sin$ cao (64.813... if 9.93 used)
3	(iii)	a.c. moments about A to find NR, $R$ , at B $R \times 0.8 = 9.93$ or $R \times 0.8 + 60\sin 40 \times 0.1 - 60\cos 40 \times 0.3 = 0$  $R = 12.4150\dots$ Resolve vertically $Y - 60 + R\cos 40 = 0$ so $Y = 50.489\dots$ so 50.5 N (3 s. f.)	M1  A1  depM1 A1 <b>[4]</b>	Attempt to use moments to find $R$ . Moments of all attempted. No extra terms. Allow $\cos \leftrightarrow \sin$ Not score M1 only if mmt of horiz compt of force at A If $R$ is taken as vertical, M0 FT their moment of weight from (i) Not a required answer  Note that the second M mark awarded in this part method to find $Y$ : FT their calculated $R$

3	Question	Answer	Marks	Guidance
	(iv)	resolve perp to plane $R - 60 \cos 40 - 200 \sin 40 = 0$  $R = 174.52\dots$ N2L up the plane $200 \cos 40 - F - 60 \sin 40 = \frac{60}{9.8} \times 1.75$  $F = 103.927\dots$ As friction limiting $F = \mu R$ so  $\mu = \frac{103.927\dots}{174.520\dots}$ $= 0.59550\dots$ so 0.596 (3 s. f.)	M1 A1  M1 B1 A1 A1  M1  A1 <b>[8]</b>	All terms present and no extra terms. allow $\cos \leftrightarrow \sin$  Not a required answer  Use of N2L with all terms present and no extra terms and 200; allow $\cos \leftrightarrow \sin$ Allow use of 60 for mass Use of mass not weight FT use of weight and/or sign errors All correct. Not a required answer  FT their $F$ and their $R$  cao

Question	Answer	Marks	Guidance
4 (a) (i)	Write $d = 0.8$ $(2.5 + 1.2 + 1.3 + 2.4) \times d \times \begin{pmatrix} \bar{x} \\ \bar{y} \end{pmatrix}$ $= 2.5d \begin{pmatrix} 1.2 \\ -0.35 \end{pmatrix} + 1.2d \begin{pmatrix} 2.4 \\ -0.1 \end{pmatrix} + 1.3d \begin{pmatrix} 1.8 \\ 0.25 \end{pmatrix} + 2.4d \begin{pmatrix} 1.2 \\ 0 \end{pmatrix}$ OR: $(2 + 0.96 + 1.04 + 1.92) \times \begin{pmatrix} \bar{x} \\ \bar{y} \end{pmatrix}$ $= 2 \begin{pmatrix} 1.2 \\ -0.35 \end{pmatrix} + 0.96 \begin{pmatrix} 2.4 \\ -0.1 \end{pmatrix} + 1.04 \begin{pmatrix} 1.8 \\ 0.25 \end{pmatrix} + 1.92 \begin{pmatrix} 1.2 \\ 0 \end{pmatrix}$ $7.4 \begin{pmatrix} \bar{x} \\ \bar{y} \end{pmatrix} = \begin{pmatrix} 3 + 2.88 + 2.34 + 2.88 \\ -0.875 - 0.12 + 0.325 + 0 \end{pmatrix} = \begin{pmatrix} 11.1 \\ -0.67 \end{pmatrix}$ OR: $5.92 \begin{pmatrix} \bar{x} \\ \bar{y} \end{pmatrix} = \begin{pmatrix} 2.4 + 2.304 + 2.304 + 1.872 \\ -0.7 - 0.096 + 0.26 + 0 \end{pmatrix} = \begin{pmatrix} 8.88 \\ -0.536 \end{pmatrix}$ $\bar{x} = 1.5$ $\bar{y} = -0.090540... = -0.0905 \text{ (3 s. f.)}$	M1 B1 B1 E1 A1 <b>[5]</b>	Method for c.m (length is 7.4 m, mass is ...) One rod mass and cpts correct or if done by se equations 2 rod components and masses corre instead of mass) Another rod dealt with correctly or if done by equations, the other equation attempted with 2 masses correct. (Allow length used instead of ...) Clearly shown, with at least one intermediate s Condone - 0.09

Question			Answer	Marks	
4	(a)	(ii)	EITHER: New c.m. has $\bar{x} = 1.2$ $(5.92 + m) \times 1.2 = 5.92 \times 1.5 + m \times 0$ $m = 1.48$	M1 M1 A1 [3]	Identifying and using a suitable condition Complete method cao
			OR: Moment about any point is zero e.g. about S: $1.2mg = 0.3 \times 5.92g$ $m = 1.48$	M1 M1 A1 [3]	Identifying a suitable condition. Allow g omitted. Correct number of terms must be used cao
4	(b)	(i)	Consider the equilibrium at R Resolving horizontally gives $T_{QR} = 0$ Then resolving vertically gives $T_{OR} = 0$	E1 E1 [2]	
4	(b)	(ii)	c.w. moments about O $120 \times 1 + 60 \times 2 = 3T$ so $T = 80$ Resolve to give $X = 80$ and $Y = 180$	M1 A1 A1 [3]	May also be argued by first considering internal forces FT $X = T$ . Only $Y = 180$ scores 0
4	(b)	(iii)		B1 [1]	All correct. Accept $T, X$ and $Y$ labelled but not mixed mixes of T and C. Require pairs of arrows with labels and PQ.
4	(b)	(iv)	Take angle OPQ as $\alpha$ At P $\downarrow 60 + T_{OP} \sin \alpha = 0$  $\sin \alpha = \frac{3}{\sqrt{13}} : \alpha = 56.3^\circ$  $T_{OP} = -\frac{60}{\sin \alpha} = -20\sqrt{13}$ so $20\sqrt{13}$ N (C) At P $\leftarrow T_{QP} + T_{OP} \cos \alpha = 0$ so $T_{QP} = 40$ so 40 N (T)	M1 A1  A1 M1 A1 [5]	Forces internal to the rods have been taken to be zero Equilibrium at ANY pin-joint (not R) Correct equation(s) that leads directly to finding $T$  o.e. Accept 72.1 N A second equilibrium equation leading to a second value for $T$ cao T/C correct for both rods

**OCR (Oxford Cambridge and RSA Examinations)**  
1 Hills Road  
Cambridge  
CB1 2EU

**OCR Customer Contact Centre**

**Education and Learning**

Telephone: 01223 553998

Facsimile: 01223 552627

Email: [general.qualifications@ocr.org.uk](mailto:general.qualifications@ocr.org.uk)

**[www.ocr.org.uk](http://www.ocr.org.uk)**

For staff training purposes and as part of our quality assurance programme your call may be recorded or monitored

**Oxford Cambridge and RSA Examinations**  
is a Company Limited by Guarantee  
Registered in England  
Registered Office; 1 Hills Road, Cambridge, CB1 2EU  
Registered Company Number: 3484466  
OCR is an exempt Charity

**OCR (Oxford Cambridge and RSA Examinations)**  
Head office  
Telephone: 01223 552552  
Facsimile: 01223 552553

© OCR 2013

